



17-4PH stainless steel.  
Suitable for the pricing scales, bench scales etc.  
Recommended platform size:400x400mm

Capacity	Accuracy	Part number
100kg	C3	B6E-C3-100kg-2B
150kg	C3	B6E-C3-150kg-2B
200kg	C3	B6E-C3-200kg-2B
300kg	C3	B6E-C3-300kg-2B

**Specifications**

Accuracy Class	C3	Temperature effect on span (%FS/10 )	0.014
Rated output (mV/V)	2.0 ± 0.02	Temperature effect on zero (%FS/10 )	0.017
Combined error (%FS)	0.02	Temperature, Compensated ( )	- 10- + 40
Non-linearity (%FS)	0.017	Temperature, Operating ( )	- 35- + 65
Non-repeatability (%FS)	0.01	Excitation, Recommended (V)	5-12(DC)
Creep (%FS/30min)	0.015	Excitation, Max.( V)	18(DC)
Input Resistance ( )	406 ± 6	Safe Overload (%FS)	150
Output Resistance ( )	350 ± 3	Ultimate Overload (%FS)	300
Insulation Resistance (M )	≥5000(50VDC)	Protection Class	IP 65
Zero Balance (%FS)	2.0	Cable Length (m)	2
Off center load error (% , per OIML R76)	0.02	Cable spec	4-wire shielded cable 5.3mm

Connections Red Input (+) Black Input (-) Green Output(+) White Output(-) Transparence (shield)

**Outline Dimensions in mm(inches)**

